

## LIFT DESCRIPTION

The BKG Advantage range of off-the-shelf dumbwaiter service lifts considerably reduce delivery times and maintain the high standard of quality engineering BKG are renowned for. Available in two different size options with a stainless-steel car as standard. The lifts are installed within a galvanised steel structure that requires cladding by others.

The BKG Advantage dumbwaiters have a traction drive system and can be installed with either a three-phase or single-phase power supply. Completely self-contained, there is no need to form a recessed pit or machine room and 2-hour fire-rated landing doors are a standard feature.

Ideal for pubs, restaurants, commercial kitchens and private homes BKG advantage dumbwaiters provide maximum reliability and durability and excellent value for money.

## FEATURES

- Up to 7.2 m (three stops).
- Stainless-steel lift car.
- Quick delivery and installation.
- 2-Hour fire-rated stainless steel landing doors.
- No recessed pit or separate machine room.

## MANUFACTURING STANDARDS

**European machine directive 2006/42/EC**  
**BS EN81-3:2001**  
**CE Marked**

## GENERAL INFORMATION

Colour:	Stainless-steel
Range:	Two standard sizes and load capacities available
Solution:	Ideal for pubs, restaurants, commercial kitchens and private homes
Finish:	Stainless-steel
Shape:	Rectangular
Configurations:	Single or Through
CAWS:	X12/110 Vertical Lifting Platform Systems

## CAR SIZES

460 wide x 570 deep x 800 high mm, 50 kg  
 750 x 750 mm structural opening.

710 wide x 820 deep x 800 high mm, 50 kg  
 1000 x 1000 mm structural opening.

## CONSOLE HEIGHT

1500mm

## HANDRAIL

No handrail

## FLOORING:

Removable mid-shelf  
 Heated car floor

**DESTINATION BUTTONS**

Call and send

**COMMUNICATION**

Option for 2-way Intercom

**SHAFT CONSTRUCTION**

Galvanised steel

**DOORS****Type:**

2-Hour fire-rated vertical bi-parting shutter landing doors  
 Vertical bi-parting car shutter  
 Brushed aluminium roller shutter car door

**Colour:**

Stainless-steel

**Accessories:**

Additional auxiliary main contactor  
 Phase failure reversal relay  
 Position indicator  
 Lift in use indicator  
 Lift arrival buzzer  
 Anti quick-reversal  
 Overtravel timer  
 Hand lamp  
 Light and socket within machine room  
 Wiring in loom form  
 Lockable machine room access door – Stainless-steel 2-hour fire-rated  
 Additional landing entrance assemblies – 2-hour fire-rated  
 Heated car floor  
 Additional car shelves  
 Machine room access ladder  
 Brushed aluminium Roller Shutter for car entrance fitted with electrical contact  
 Stainless Steel Bi-Parting Shutter for car entrance fitted with electrical contact  
 Note: the fitting of car doors will reduce the usable space inside the car

**STANDARD PRODUCT FEATURES****Size:**

Serving Height: 800mm  
 Door Size: Car width x 800mm high  
 Travel Height: 6000mm (2 stops) 7200mm (3 stops)  
 Top Height/Headroom: 2600mm

**Technical Properties:**

Drive System: Traction drive  
 Rated Speed: 0.45 m/s  
 Landing Control: One-touch call  
 Landing Control: One-touch run  
 Technical Compliance: European Machine Directive 2006/42/EC  
 Number of Stops (Max) : Three  
 Number of Doors (Max): One per floor  
 Pit Recess: 0 mm (No pit required)  
 Control Supply: 24 Volts

**PRODUCT OPTIONS****Size/Rated Load/Power:**

50 kg rated load: Three-phase 400 V 50Hz, or Single-phase  
 100 kg rated load: Three-phase 400 V 50Hz, or Single-phase